

Braille Battery XCEL-Lite



Part Number	Polarity	Amp Hour	Voltage	Dimensions (L/W/H) (MM)	Weight (KG)	10s Pulse Discharge Current (A)	Continuous Discharge Current (A)	Terminal Type
XC10.0-500L	Right +	10	12V	150/88/145	1.8	500	200	Brass Terminal Block with M6 Bolt
XC12.5-625L	Right +	12.5	12V	150/88/145	2.2	625	250	Brass Terminal Block with M6 Bolt
XC12.5-625-1	Right +	12.5	12V	178/76/159	2.1	625	250	Brass Terminal Block with M6 Bolt
XC15.0-750	Right +	15	12V	178/76/159	2.5	750	300	Brass Terminal Block with M6 Bolt
XC15.0-750-1	Right +	15	12V	174/132/177	2.9	750	300	Brass Terminal Block with M6 Bolt
XC15.0-750-2	Right +	15	12V	248/96/154	3	750	300	Brass Terminal Block with M6 Bolt
XC20.0-1000	Right +	20	12V	174/132/177	3.7	1000	400	Brass Terminal Block with M6 Bolt
XC20.0-1000-1	Right +	20	12V	248/96/154	3.7	1000	400	Brass Terminal Block with M6 Bolt
XC20.0-1000-2	Right +	20	12V	248/96/205	3.8	1000	400	Brass Terminal Block with M6 Bolt
XC20.0-1000-3	Right +	20	12V	239/173/203	4.5	1000	400	Brass Terminal Block with M6 Bolt
XC22.5-1125M6	Right +	22.5	12V	258/80/156	4	1125	450	M6 Stud
XC25.0-1250	Right +	25	12V	174/132/177	4.2	1250	500	Brass Terminal Block with M6 Bolt
XC25.0-1375-C	Right +	25	12V	248/96/205	4.5	1375	500	Brass Terminal Block with M6 Bolt
XC30.0-H	Right +	30	12V	174/132/177	4.2	600	300	Brass Terminal Block with M6 Bolt
XC50.0-2750-C	Right +	50	12V	279/173/195	9	2750	1000	SAE Terminals
XC24.0-950	Left +	24	16V	254/83/156	4	950	240	3/8" Stud
XC20.0-2325	Left +	20	16V	254/83/156	4	2325	400	3/8" Stud

Accessories

Description	Part Number	Fits
Bracket	3118	XC15.0-750-1 XC25.0-1250-C
Bracket	2218	XC12.5-625-1
Bracket (Vertical Mount)	211	XC12.5-625-1 XC15.0-750-C
Bracket	6188	
Brass Terminals (M6 Pair)	2012K	
Lithium Charger (6AH)	1236L	
Lithium Charger (10AH)	12310L	
Lithium Charger (25AH)	12325L	

MOTORVISION_23

Pesos e dimensões indicativas e aproximadas

+351 234 029 672 # +351 919 002 122

motorvision@motorvision.pt

motorvision@motorvision-race.com

